



12.1.5. Cable Tray Internal Risers

Product Overview:


Hitech provides 90° Inside Riser in standard thickness for industrial applications that ranges from 1mm to 2mm, depending on the load requirement.

90° Inside Riser are made up of metal with a series of uniform holes (perforations) along their base and sides. These perforations provide excellent support for cables while allowing ventilation to reduce heat buildup.

At Hitech, 90° Inside Risers are available in a variety of widths, from 150mm up to 900mm or more as per customer requirements, to accommodate different cable bundle sizes and flange height ranges from 50mm to 100mm, selected based on the required cable capacity. This design meets industry standards (e.g., NEMA VE-1, IEC 61537) for load-bearing capacity, fire resistance, and durability.

Technical Specifications:

Material	Hot Rolled Steel Sheet to BS 1449
Strength	Light, Medium and Heavy Duty



Features:

- Protects cables from damage during vertical transitions.
- Durable construction resists environmental factors and mechanical stress.
- Compatible with various tray systems for seamless integration.
- Easy to install, saving time and effort.

12.1.5.3. Heavy Duty-Cable Tray Internal Riser (Thickness: 2mm)

Product Code	Tray Type	H (mm)	W (mm)	Th (mm)
HTPIR75/400-20	IF/PL	75	400	2
HTPIR100/400-20	IF/PL	100	400	2
HTPIR50/450-20	IF/PL	75	450	2
HTPIR100/450-20	IF/PL	100	450	2
HTPIR100/500-20	IF/PL	100	500	2
HTPIR100/600-20	IF/PL	100	600	2
HTPIR100/700-20	IF/PL	100	700	2
HTPIR100/800-20	IF/PL	100	800	2
HTPIR100/900-20	IF/PL	100	900	2

*Note: Customized Sizes are Available

Tray Type	
Inside Flanged (IF)	Plain (PL)

Coating Types	
HDG	Hot Dip Galvanized
GI	Pre-Galvanized
AL	Aluminum
P. C.	Powder Coated

