



12.2.5. Cable Tray Internal Riser


Product Overview:

Hitech provides 90° Inside Riser in standard thickness for industrial applications that ranges from 1mm to 2mm, depending on the load requirement. This innovative provides excellent support for cables while allowing ventilation to reduce heat buildup.

At Hitech, 90° Inside Risers are available in a variety of widths, from 50mm up to 900mm or more as per customer requirements, to accommodate different cable bundle sizes and flange height ranges from 50mm to 100mm, selected based on the required cable capacity. This design meets industry standards (e.g., NEMA VE-1, IEC 61537) for load-bearing capacity, fire resistance, and durability.

Features:

- Protects cables from damage during vertical transitions.
- Durable construction resists environmental factors and mechanical stress.
- Compatible with various tray systems for seamless integration.
- Easy to install, saving time and effort.



Technical Specifications:

Material	Hot Rolled Steel Sheet to BS 1449
Strength	Light, Medium and Heavy Duty

12.2.5.2. Medium Duty- Riser Cable Tray (Thickness: 1.5mm)

Product Code	Tray Type	H (mm)	W (mm)	Th (mm)
HTTIR50/200-15	IF/PL	50	200	1.5
HTTIR75/200-15	IF/PL	75	200	1.5
HTTIR100/200-15	IF/PL	100	200	1.5
HTTIR50/250-15	IF/PL	50	250	1.5
HTTIR75/250-15	IF/PL	75	250	1.5
HTTIR100/250-15	IF/PL	100	250	1.5
HTTIR50/300-15	IF/PL	50	300	1.5
HTTIR75/300-15	IF/PL	75	300	1.5
HTTIR100/300-15	IF/PL	100	300	1.5

*Note: Customized Sizes are Available

Tray Type	
Inside Flanged (IF)	Plain (PL)

Coating Types	
HDG	Hot Dip Galvanized
GI	Pre-Galvanized
AL	Aluminum
P. C.	Powder Coated

